

CW29SVL LIQUID SOAP DISPENSER

INSTALLATION INSTRUCTIONS

INSTALLING DISPENSER:

- 1) INSERT THREADED SHANK INTO HOLE SO THAT RUBBER WASHER(17) IS BETWEEN BASIN AND SHOULDER OF SHANK.
- 2) PLACE WASHER(18) ON SHANK AND SCREW NUT(16) ON TO SHANK. TIGHTEN NUT SO THAT SHANK IS HELD SECURELY TO BASIN. DO NOT OVER TIGHTEN NUT.
- 3) REMOVE PISTON ASSEMBLY BY UNSCREWING COLLAR(4) AND LIFTING ASSEMBLY UPWARD. USE SERVICE WRENCH PROVIDED.
- 4) INSERT SUPPLY TUBE(11) OVER END OF CYLINDER(9).
- 5) REPLACE PISTON ASSEMBLY INTO SHANK HOUSING AND TIGHTEN COLLAR HAND TIGHT.
- 6) INSTALL GLOBE SO THAT SUPPLY TUBE IS APPROXIMATELY 1/4" AWAY FROM BOTTOM OF GLOBE. TIGHTEN SCREW ON GLOBE COLLAR(19&20). THIS WILL PREVENT SEDIMENT FROM BEING DRAWN UP INTO THE DISPENSING MECHANISM.

FILLING DISPENSER:

- 1) UNSCREW COLLAR(4) WITH SERVICE WRENCH. COLLAR UNSCREWS IN A COUNTER-CLOCKWISE DIRECTION WHEN LOOKING DOWN ON DISPENSER.
- 2) LIFT OUT ENTIRE VALVE ASSEMBLY FROM SHANK HOUSING
- 3) POUR LIQUID SOAP INTO OPEN TOP OF SHANK UNTIL CONTAINER BELOW BASIN IS FILLED.
10-20% COCONUT OIL LIQUID HAND SOAP SHOULD BE USED.
- 4) REPLACE VALVE ASSEMBLY AND TIGHTEN COLLAR WITH WRENCH.
NOTE: IT IS NOT NECESSARY TO REMOVE THE SOAP CONTAINER WHEN FILLING THIS DISPENSER.

OPERATION:

TO PRIME DISPENSER WHEN USING FOR THE FIRST TIME, COVER SPOUT OPENING WITH FINGER ON THE UP-STROKE OF PLUNGER UNTIL SOAP STARTS TO FLOW. (REMOVE FINGER ON DOWN-STROKE.)

MAINTENANCE:

A LITTLE LIQUID SOAP ON A WET CLOTH IS YOUR BEST POLISHING AGENT. AVOID THE USE OF ABRASIVE CLEANERS. CLEAN THE SPOUT NOZZEL AND ALL SURFACES DAILY.

CW29SVL PARTS PRICE LIST

DRAWING NO.	PART NUMBER	DESCRIPTION
1&2	CW29SV-17	PISTON AND 2 1/2" SPOUT
1&2	CW29SV-17L	PISTON AND 4" SPOUT
1&2	CW29SV-17LM	PISTON AND 6" SPOUT
3	CW29SV-88	DUCK BILL
4	CW29SV-4	COLLAR
5	CW29SV-9	CHECK VALVE
6	CW29SV-69	SPACER
7	CW29SV-8	SPRING
8	CW29SV-71	S.S. RING
9	CW29SV-74	CYLINDER
10	CW29SV-19	O-RING
11	CW29SV-20	TUBE
12	CW29SV-72	SET SCREW
13	CW29SV-62	ABS SHANK
14	CW29SV-34	POLY GLOBE
15	CW29SV-26	KEY
16	CW29SV-22	HEX NUT
17	CW29SV-25	RUBBER WASHER
18	CW29SV-21	S.S. WASHER
19&20	CW29SV-36	GLOBE COLLAR/SCREW

